



TECHNICAL PRODUCT SPECIFICATIONS
LUXURY VINYL TILE
ESSENCE PLANK DRY BACK

SPECIFICATIONS:

STYLE NAME	ESSENCE PLANK DRY BACK
FINISH	PU LACQUER
EMBOSSMENT	SOFT WOOD EMBOSS
BEVEL	4 SIDED MICRO BEVEL
NOMINAL WEAR LAYER THICKNESS	22 MILS (0.55 MM)
NOMINAL PRODUCT THICKNESS	2.3 MM
NOMINAL PLANK SIZE	7.01" W X 49.21"L X .09" H
PIECES PER CARTON	15
SQUARE FEET PER CARTON	35.93 SQ. FT.
APPROX. WEIGHT PER CARTON	21.05 LBS.
CARTON SIZE	49.65" L X 7.48" W X 1.54" H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	2,012.08 SQ. FT.
APPROX. WEIGHT PER PALLET	1,228.80 LBS.
PALLETS PER 40 FT. CONTAINER	35
SQUARE FEET PER 40 FT. CONTAINER	70,422.80 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	43,008 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN SLOVENIA

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.2 K.V. OR LOWER
ORTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.64
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1300 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 56,000 CYCLES

INSTALLATION:

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	DIRECT GLUE DOWN
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO ULTRABOND LVT ADHESIVE, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
---	--

DESIGN & MATERIAL NUMBER	DRY BACK COLOR NUMBER	EAN / UPC
COLUMBIAN OAK 226M	60000593	5414404172204
LIME OAK 623M	60000604	5414404172310
LIME OAK 669M	60000605	5414404172327
LIME OAK 954D	60000608	5414404172358
LIME OAK 966D	60000610	5414404172372
LIME OAK 996D	60000613	5414404172402
TOULON OAK 293M	60000616	5414404172433
TOULON OAK 976M	60000619	5414404172464

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop

877.362.5562

One Beauflor Way
White, GA 30184
United States

beauflor.us