



TECHNICAL PRODUCT SPECIFICATIONS
CUSHION VINYL SHEET
JAZZ

SPECIFICATIONS:

STYLE NAME	JAZZ
FINISH	PU LACQUER
PATTERN REPEAT	ALL OVER
NOMINAL WEAR LAYER THICKNESS	16 MILS (0.4 MM)
NOMINAL PRODUCT THICKNESS	80 GAUGE (2 MM)
BACKING TYPE	POWER BAC
AVAILABLE WIDTH	13'2"
STANDARD ROLL LENGTH (TOLERANCES APPLY)	98 FT.
WEIGHT PER SQUARE YARD	2.95 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 2 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.2 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF - DRY 0.70
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 10,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	100% RECLAIMABLE

INSTALLATION:

END USE:	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD:	DIRECT GLUE DOWN
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO HS RESILIENT SPRAY, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, BEAUFLO CV SEAM SEALER.

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR, MANUFACTURING DEFECT WARRANTY
---	--

DESIGN & MATERIAL NUMBER

13' 2'

PATTERN REPEAT

DESIGN & MATERIAL NUMBER	13' 2'	PATTERN REPEAT
LIANA 009L	50035068	ALL OVER
LIANA 111L	50035067	ALL OVER
LIANA 199L	50035064	ALL OVER
LIANA 663L	50035066	ALL OVER
LIANA 691M	50035065	ALL OVER
LIANA 797D	50035062	ALL OVER
LIANA 909M	50035061	ALL OVER
LIANA 919M	50035063	ALL OVER
LIANA 999D	50035048	ALL OVER

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop