



**TECHNICAL PRODUCT SPECIFICATIONS  
RIGID COMPOSITE VINYL PLANK  
PURE PLANK**

**SPECIFICATIONS:**

STYLE NAME	PURE
LOCKING SYSTEM	DREAMCLICK
FINISH	SOFT WOOD /SAND EMBOSS
BEVEL	4 SIDED MICRO BEVEL
NOMINAL WEAR LAYER THICKNESS	22 MIL (0.55MM)
NOMINAL PRODUCT THICKNESS	5.0 MM (0.2 in)
NOMINAL PLANK SIZE	8.03" W X 52.20" L X 0.20" H
PIECES PER CARTON	8
SQUARE FEET PER CARTON	23.29 SQ. FT.
APPROX. WEIGHT PER CARTON	27.56 LBS.
CARTON SIZE	8.82" W X 53.39" L X 1.61" H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	1,304.24 SQ. FT.
APPROX. WEIGHT PER PALLET	1,593.36 LBS.
PALLETS PER 40 FT. CONTAINER	27
SQUARE FEET PER 40 FT. CONTAINER	35,214.48 SQ. FT
APPROX. WEIGHT PER 40 FT. CONTAINER	43,020.72 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

**PERFORMANCE:**

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
OTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.74
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1200 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2753 ROLLING LOADS - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 38,000 CYCLES
ASTM E492 - IIC RATING 62	

**INSTALLATION:**

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED	UNDERLAYMENT NO MORE THAN 1.5 MM THICKNESS

**WARRANTIES:**

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR AND MANUFACTURING DEFECT WARRANTY
---	---

DESIGN & MATERIAL NUMBER	EAN/UPC	PART NUMBER
TOULON OAK PEARL 109S	5414404151698	60000108
TOULON OAK MINK 976M	5414404151735	60000112
TOULON OAK FLAXEN 069L	5414404234759	60001624
LIME OAK SADDLE 669M	5414404151827	60000121
LIME OAK ASH 996D	5414404151858	60000124
LIME OAK WALNUT 966D	5414404151865	60000125
LIME OAK COFFEE 954D	5414404157065	60000200
COLUMBIAN OAK RUSSET 226M	5414404157041	60000197
COLUMBIAN OAK MOCHA 663D	5414404157058	60000198
COLUMBIAN OAK FAWN 611M	5414404234711	60001620
COLUMBIAN OAK SAND 216M	5414404234728	60001621
COLUMBIAN OAK LATTE 661M	5414404234735	60001622
COLUMBIAN OAK MIST 966M	5414404234742	60001623
AUTHENTIC OYSTER 919M	5414404234766	60001625
URBAN GUNMETAL 996D	5414404234780	60001628
URBAN LIMESTONE 166S	5414404234797	60001627

**CARE & MAINTENANCE:**

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.  
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.