



**TECHNICAL PRODUCT SPECIFICATIONS
RIGID COMPOSITE VINYL PLANK
PURE TILE**

SPECIFICATIONS:

STYLE NAME	PURE
LOCKING SYSTEM	DREAMCLICK
FINISH	SAND EMBOSS
BEVEL	4 SIDED MICRO BEVEL
NOMINAL WEAR LAYER THICKNESS	22 MILS (0.55 MM)
NOMINAL PRODUCT THICKNESS	5.0 MM (0.2 in)
NOMINAL PLANK SIZE	12.047" W X 24.09" L X 0.20" H
PIECES PER CARTON	8
SQUARE FEET PER CARTON	16.126 SQ. FT
APPROX. WEIGHT PER CARTON	19 LBS.
CARTON SIZE	24.88" L X 12.67" W X 1.69" H
CARTONS PER PALLET	56
SQUARE FEET PER PALLET	903.06 SQ. FT
APPROX. WEIGHT PER PALLET	1,114 LBS.
PALLETS PER CONTAINER	38
SQUARE FEET PER 40 FT. CONTAINER	34,316.13 SQ. FT.
APPROX. WEIGHT PER 40 FT. CONTAINER	42,332 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
OTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.74
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1200 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2753 ROLLING LOADS - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 38,000 CYCLES
ASTM E492 - IIC RATING 62	

INSTALLATION:

END USE	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED	UNDERLAYMENT NO MORE THAN 1.5 MM THICKNESS

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR AND MANUFACTURING DEFECT WARRANTY
---	---

DESIGN & MATERIAL NUMBER	EAN/UPC	PART NUMBER
ZINC UMBER 679M	5414404151469	60000085
ZINC STONE 373D	5414404151476	60000086
ZINC FOG 967M	5414404234773	60001626
NEWCASTLE DOVE 169M	5414404234803	60001629
NEWCASTLE CLAY 369M	5414404234810	60001630
NEWCASTLE SHELL 963M	5414404234827	60001631
NEWCASTLE SHADOW 796D	5414404234834	60001632
NEWCASTLE SMOKE 909M	5414404234841	60001633

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.