



TECHNICAL PRODUCT SPECIFICATIONS
CUSHION VINYL SHEET

REFLECT+

SPECIFICATIONS:

STYLE NAME	REFLECT+
FINISH	NATURQUEST- ENHANCED EMBOSS TECHNOLOGY/ PU LACQUER
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS (0.25 MM)
NOMINAL PRODUCT THICKNESS	75 GAUGE (1.9 MM)
BACKING TYPE	POWERBAC
AVAILABLE WIDTH	12'
STANDARD ROLL LENGTH	131 FT.
WEIGHT PER SQUARE YARD	2.525 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA OF GLOBAL COMPONENTS

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 3 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.8 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF- DRY .73 WET.66
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 22,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	100% RECLAIMABLE

INSTALLATION:

END USE	RESIDENTIAL
INSTALLATION METHOD	DIRECT GLUE DOWN/LOOSE LAY UP TO 25 SQ YD/225 SQ FT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO HS RESILIENT SPRAY, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, BEAUFLO CV SEAM SEALER.

WARRANTIES:

15 YEAR LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY

DESIGN	NUMBER	PATTERN REPEAT	DESIGN	NUMBER	PATTERN REPEAT
ORACLE BONE	50047607	39.37" x 39.37"	REVELATION FOSSIL	50047615	39.37" x 39.37"
ORACLE DOVE	50047608	39.37" x 39.37"	REVELATION STONE	50047614	39.37" x 39.37"
ORACLE FAWN	50047609	39.37" x 39.37"	CASTLEWOOD OAT	50047460	39.37" x 59.07"
STORYWOOD SAND	50047458	39.37" x 59.10"	CASTLEWOOD THUNDER	50047461	39.37" x 59.07"
STORYWOOD MINK	50047459	39.37" x 59.10"	FABLE OAK PEANUT	50047462	39.37" x 59.10"
MUSE PARCHMENT	50047610	98.425" x 47.244"	FABLE OAK LATTE	50047463	39.37" x 59.10"
MUSE FOG	50047611	98.425" x 47.244"	MYSTIC OAK COFFEE	50047464	39.37" x 39.37"
MUSE SHELL	50047612	98.425" x 47.244"	MYSTIC OAK SPICE	50047465	39.37" x 39.37"
MUSE CHARCOAL	50047613	98.425" x 47.244"	REGAL OAK MOCHA	50047466	78.28" x 59.10"
SPLENDOR IVORY	50047616	39.37" x 39.37"	REGAL OAK ASH	50047467	78.28" x 59.10"

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.

For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop

877.362.5562

One Beauflor Way
White, GA 30184
United States

beauflor.us