



TECHNICAL PRODUCT SPECIFICATIONS  
LUXURY SHEET VINYL  
SMARTEX PRO

**SPECIFICATIONS:**

STYLE NAME	SMARTEX PRO
FINISH	PU LACQUER
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS (0.25 MM)
NOMINAL PRODUCT THICKNESS	85 GAUGE (2.16 MM)
BACKING TYPE	TEX BAC
AVAILABLE WIDTH	12'
STANDARD ROLL LENGTH (TOLERANCES APPLY)	130 FT.
WEIGHT PER SQUARE YARD	2.78 LBS/SQ. YD.
COUNTRY OF ORIGIN	MADE IN USA OF GLOBALLY SOURCED COMPONENTS

**PERFORMANCE:**

ASTM F1303 TYPE 1 GRADE 2 CLASS A	AATCC 134 (STEP) ELECTROSTATIC 0.1 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF – DRY 0.79
CPSC-CH-C1001-09.3 PHTHALATES – MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX – CLASS 1	ASTM F137 FLEXIBILITY – PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY – UNDER 450	ASTM F925 CHEMICAL RESISTANCE – PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E – PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES

**INSTALLATION:**

END USE	RESIDENTIAL
INSTALLATION METHOD	DIRECT GLUE DOWN OR FLOAT (UNDER 250 SQ. FT. )
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, USE COLD WELD SEAM SEALER ONLY

**WARRANTIES:**

15 YEAR LIMITED RESIDENTIAL WEAR WARRANTY
---

DESIGN	NUMBER	PATTERN REPEAT	DESIGN	NUMBER	PATTERN REPEAT
MOJAVE MORNINGS DW	50044621	39.37" W x 59.10"L	BLACK LICORICE DW	50044624	39.37" W x 59.10"L
HONG KONG SUNSET DW	50044618	39.37" W x 59.10" L	STERLING HARBOR	50043971	39.37" W x 39.37"L
BARRE BEIGE	50043920	39.37" W x 39.37"L	LIGHTEN UP	50043919	39.37" W x 39.37"L
SAHARA SUNRISE DW	50044617	39.37" W x 59.10"L	MOCHA CHINO DW	50044620	39.37" W x 59.10"L
CARAMEL TOFFEE DW	50044619	39.37" W x 59.10"L	RIDGE CREST	50044623	39.37" W x 39.37"L
SAND PEAK	50044622	39.37" W x 39.37"L	PEARLY WHITES	50043921	ALL OVER

**CARE & MAINTENANCE:**

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.  
For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.